

STAR Technology

FORMULATING • INNOVATIVE • SOLUTIONS

ER7159

Secondary Insulation Impregnating Resin Water Based Hermetic Varnish

DESCRIPTION

ER7159 is a one-part heat cure epoxy emulsion in water. ER7159 contains no solvents and forms a non-dripping film coating once the water has evaporated. ER7159 was designed for use as a dipping varnish on hermetic, general purpose and compressor motors. ER7159 was formulated to use with a variety of refrigerants and compressor oils while maintaining a low extractable value. ER7159 has superior physical strength while offering excellent electrical properties. Shake or stir well before using.

Data contained herein are believed to be reliable. Fit-for-use testing should be conducted by each user.

BENEFITS

Zero VOC's

Low Extractables

Excellent Electrical Properties

PHYSICAL PROPERTIES

	<u>TEST METHOD</u>	<u>VALUE</u>
Cure Time 302°F [150°C] (hours):		4
Viscosity @ 60% Solids (cps):	ASTM D2393	300-600
Viscosity @ 50% Solids (cps):	ASTM D2393	100-200
Viscosity @ 25% Solids (cps):	ASTM D2393	20-40
Viscosity @ 37% Solids (cps):	ASTM D2393	40-60
Specific Gravity (g/cc):	ASTM D1475	1.07
Liquid Color:		White
Dry Color:		Clear
Shore Hardness (D):	ASTM D2240	80
Tg (°C):		125
Helical Coil Bond Strength [50% solids (lbs)]:	ASTM D2519	
25C:		50
150C:		31
Dielectric Breakdown Strength (V/mil):	ASTM D150	
0.3mil (V / mil)		2680
Percent Solids (%):		25-60
Service Temperature (°C):		200

PROCESSING

- Mix thoroughly before processing. **Agitate once weekly recommended while stored.**
- Pre-heat part for 1 hour at 135-150° C (275-300°F) to relax magnet wire and drive out residual moisture.
- Part temperature should be 50 - 55°C (120-130°F) before resin is introduced. Temperature is directly correlated to varnish penetration – too low varnish will not penetrate well and too high can damage varnish (advance cure).
- Submerge part slowly and hold until bubbles cease, about 10-20 minutes, to give complete penetration.
- Once the bubbles cease, raise part slowly.
- Drain for 10-15 minutes, longer if possible, allowing for less waste.
- Bake for 4-6 hours at 150°C. Full cure is necessary for development of performance properties.
- Store out of direct sunlight in a dry, cool place away from heat.

To the best of our knowledge, the information contained herein is accurate. However, STAR TECHNOLOGY, Inc., does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any material is the sole responsibility of the user. The information contained herein is considered typical properties and is not intended to be used as specifications for our products. This information is offered solely to assist purchaser in selecting the appropriate products for purchaser's own testing. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein and in the material safety data sheet, we cannot guarantee that these are the only hazards that exist. Repeated and prolonged exposure to epoxy resins can cause sensitization or other allergic responses.

STAR Technology

FORMULATING • INNOVATIVE • SOLUTIONS

ER7159

Secondary Insulation Impregnating Resin Water Based Hermetic Varnish

Dilution Chart of Water to obtain different percentages of ER7159 - 60%

Please use Distilled or R/O Water

		Gallons of Water to Add		
		<u>50%</u>	<u>37.5%</u>	<u>25%</u>
1 Drum	50 Gallons	11	33	76
2 Drums	100 Gallons	22	65	152
5 Drums	250 Gallons	54	163	380
10 Drums	500 Gallons	119	326	760

Percentages of ER7159 - 50%

		<u>37.5%</u>	<u>25%</u>
1 Drum	50 Gallons	20	57
2 Drums	100 Gallons	40	113
5 Drums	250 Gallons	99	283
10 Drums	500 Gallons	198	565

Percentages of ER7159 – 37.5%

		<u>25%</u>
1 Drum	50 Gallons	25
2 Drums	100 Gallons	50
5 Drums	250 Gallons	124
10 Drums	500 Gallons	249

PRECAUTIONS

For industrial use only. Keep away from children. Refer to the Safety Data Sheets (SDS forms) pertaining to this product before using. Avoid contact with skin or eyes. In the event of an eye splash or contact, immediately flush with cold water for 15 minutes and contact a physician. If skin contact occurs, wash with mild soap and water. The wearing of safety glasses with side shields and impervious gloves is recommended.

RESIN AND HARDENER WARNING STATEMENT

May cause allergic skin reaction. Avoid all contact with skin, eyes, and clothing. Wash thoroughly after handling.

To the best of our knowledge, the information contained herein is accurate. However, STAR TECHNOLOGY, Inc., does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any material is the sole responsibility of the user. The information contained herein is considered typical properties and is not intended to be used as specifications for our products. This information is offered solely to assist purchaser in selecting the appropriate products for purchaser's own testing. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein and in the material safety data sheet, we cannot guarantee that these are the only hazards that exist. Repeated and prolonged exposure to epoxy resins can cause sensitization or other allergic responses.